

Batteriekontakt / Battery Probe - UEBK-12548

Material (Material)

Gehäuse: Schwarz PA9T (UL94V-0)

(Frame: Black PA9T UL94V-0)

Kolben: Messing

(Plunger: Brass)

Stifthülse: Messing

(Barrel: Brass)

Feder: Edelstahl

(Spring: Stainless Steel)

Beschichtung: Nickel, vergoldet

(Plating: Au over Ni)

Elektrische Spezifikation (Electrical specification)

Nennstrom: 1 A

(Rated Current: 1 A)

Kontaktwiderstand: < 50 mΩ

(Contact Resistance: < 50 mΩ)

Mechanische Spezifikation (Mechanical specification)

Kontakte: 2

(No. of contacts: 2)

Minimum Raster: 2,54 mm

(Minimum Centers: 2,54 mm)

Max Hub: 1,6 mm

(Max. travel: 1,6 mm)

empfohlener Hub: 0,8 mm

(Recommended travel: 0,8 mm)

Federkraft: 1,2 N bei Nennfederweglänge

(Spring Force: 1,2 N @ working height)







Anschluss: SMD

(Connection: SMD)

Bestellinformation (Order Information)

Kontakt (Probe):

UEBK-12548



Änderungen und Irrtümer vorbehalten. Angaben in Millimeter (mm) / Specifications subject to change without notice. Dimensions in Millimeter (mm)