

Batteriekontakt / Battery Probe - UEBK-12553

Material (Material)

Gehäuse: PBT + GF 30% (UL94V-0)

(Housing: PBT + GF 30% (UL94V-0))

Kolben: Messing, vergoldet

(Plunger: Brass, gold plated)

Stifthülse: Messing, vergoldet

(Barrel: Brass, gold plated)

Feder: Edelstahl

(Spring: Stainless Steel)

Elektrische Spezifikation (Electrical specification)

Nennstrom: 1 A

(Rated Current: 1 A)

Kontaktwiderstand: < 40 mΩ

(Contact Resistance: < 40 mΩ)

Mechanische Spezifikation (Mechanical specification)

Kontakte: 8

(No. of contacts: 8)

Max. Hub: 1,8 mm / voreilend 2,3 mm

(Max. travel: 1,8 mm / leading contact 2,3 mm)

Empfohlener Hub: 1,4 mm / voreilend 1,9 mm

(Recommended travel: 1,4 mm / leading contact 1,9 mm)

Federkraft: 0,35 N – 0,55 N bei Empfohlenem Hub

(Spring Force: 0,35 N – 0,55 N @ recommended travel)

Anschluss: Leiterplatte 90°

(Connection: Through hole mount 90°)

Bestellinformation (Order Information)

Art. Nr. (Art. No.):

UEBK-12553

