

## Batteriekontakt / Battery Probe - UEBK-12644

### Material (Material)

Gehäuse: Thermoplastik (UL94V-0)

(*Frame: Thermoplastic UL94-0*)

Kolben: Messing, vergoldet

(*Plunger: Brass, gold plated*)

Stifthülse: Messing, vergoldet

(*Barrel: Brass, gold plated*)

Feder: Kupfer-Beryllium

(*Spring: Copper-Beryllium*)

### Elektrische Spezifikation (Electrical specification)

Nennstrom: 2 A

(*Rated Current: 2 A*)

Kontaktwiderstand: < 20 mΩ

(*Contact Resistance: < 20 mΩ*)

### Mechanische Spezifikation (Mechanical specification)

Kontakte: 3

(*No. of contacts: 3*)

Minimum Raster: 2,54 mm

(*Minimum Centers: 2,54 mm*)

Max Hub: 1,4 mm

(*Max. travel: 1,4 mm*)

Empfohlener Hub: 0,7 mm

(*Recommended travel: 0,7 mm*)

Federkraft: 0,6 N bei Empfohlenem Hub

(*Spring Force: 0,6 N @ recommended travel*)

Anschluss: THT

(*Connection: THT*)

### Bestellinformation (Order Information)

Art. Nr. (Art. No.):

UEBK-12644

