

Batteriekontakt / Battery Probe – UEBK-13581

Material (Material)
<u>Kolben:</u> Kupfer-Beryllium, vergoldet (<i>Plunger: Copper-Beryllium, gold plated</i>) <u>Stifthülse:</u> Phosphor Bronze, vergoldet (<i>Barrel: Phosphor Bronze, gold plated</i>) <u>Feder:</u> Edelstahl (<i>Spring: Stainless Steel</i>) <u>Hülse:</u> Phosphor-Bronze / Messing (<i>Receptacle: Phosphor-Bronze / Brass</i>)
Elektrische Spezifikation (Electrical specification)
<u>Nennstrom:</u> 3 A (<i>Rated current: 3 A</i>)
Mechanische Spezifikation (Mechanical specification)
<u>Minimum Raster:</u> 0,55 mm (<i>Minimum Centers: 0,55 mm</i>) <u>Max. Hub:</u> 0,60 mm (<i>Max. travel: 0,60 mm</i>) <u>Empfohlener Hub:</u> 0,45 mm (<i>Recommended travel: 0,45 mm</i>) <u>Federkraft:</u> 0,22 N bei Empfohlenem Hub (<i>Spring Force: 0,22 N @ recommended travel</i>)
Bestellinformation (Order information)
Art. Nr.: UEBK-13581 (<i>Art. No.: UEBK-13581</i>)

