

Batteriekontakt / Battery Probe - UEBK-13803

Material (Material)

Gehäuse: Thermoplastik (UL94V-0)

(Frame: Thermoplastic UL94V-0)

Kolben: Messing, vergoldet

(Plunger: Brass, gold plated)

Stifthülse: Messing, vergoldet

(Barrel: Brass, gold plated)

Feder: Kupfer-Beryllium

(Spring: Copper-Beryllium)

Elektrische Spezifikation (Electrical specification)

Nennstrom: 2 A

(Rated current: 2 A)

Kontaktwiderstand: < 20 mΩ

(Contact resistance: < 20 mΩ)

Mechanische Spezifikation (Mechanical specification)

Kontakte: 2

(No. of contacts: 2)

Minimum Raster: 2,54 mm

(Minimum Centers: 2,54 mm)

Max. Hub: 1,4 mm

(Max. travel: 1,4 mm)

Empfohlener Hub: 0,7 mm

(Recommended travel: 0,7 mm)

Federkraft: 0,6 N bei empfohlenem Hub

(Spring Force: 0,6 N @ recommended travel)

Anschluss: THT

(Connection: THT)

Bestellinformation (Order information)

Art. Nr.: UEBK-13803

(Art. No.: UEBK-13803)

