

Batteriekontakt / Battery Probe - UEBK-30252 / 30253

Material (Material)

Gehäuse: Polyamid PA66 (UL94V-2)
(Housing: Polyamide PA66 (UL94V-2))

Kolben: Messing, vergoldet
(Plunger: Brass, gold plated)

Stifthülse: Messing, vergoldet
(Barrel: Brass, gold plated)

Feder: Edelstahl
(Spring: Stainless Steel)

Elektrische Spezifikation (Electrical specification)

Nennstrom pro Kontakt: 6 A
(Rated Current per Contact: 6 A)

Kontaktwiderstand: < 25 mΩ
(Contact Resistance: < 25 mΩ)

Mechanische Spezifikation (Mechanical specification)

Kontakte: 2
(No. of contacts: 2)

Max. Hub: 2,65 mm
(Max. travel: 2,65 mm)

Empfohlener Hub: 1,55 mm
(Recommended travel: 1,55 mm)


Federkraft pro Kontakt: 1,2 N bei Empfohlenem Hub
(Spring Force per Contact: 1,2 N @ recommended travel)

Kabelquerschnitt: max. 1,4 mm²
(Cable cross section: max. 1,4 mm²)

Bestellinformation (Order Information)

Art. Nr. *(Art. No.):*
 UEBK-30252 / UEBK-30253

UEBK-30253



UEBK-30252

