

Batteriekontakt / Battery Probe - UEBK-30285 / 30286

Material (Material)

Gehäuse: Polyamid PA66 (UL94V-2)

(Frame: Polyamide PA66 (UL94V-2))

Kolben: Messing, vergoldet

(Plunger: Brass, gold plated)

Stifthülse: Messing, vergoldet

(Barrel: Brass, gold plated)

Feder: Edelstahl

(Spring: Stainless Steel)

Elektrische Spezifikation (electrical specification)

Nennstrom pro Kontakt: 6 A

(Rated Current per Contact: 6 A)

Kontaktwiderstand: < 25 mΩ

(Contact Resistance: < 25 mΩ)

Mechanische Spezifikation (mechanical specification)

Kontakte: 3

(No. of contacts: 3)

Max. Hub: 2,65 mm

(Max. travel: 2,65 mm)

Empfohlener Hub: 1,55 mm

(Recommended travel: 1,55 mm)

Federkraft pro Kontakt: 1,2 N bei Empfohlenem Hub

(Spring Force per Contact: 1,2 N @ recommended travel)

Für Kabel: max. 1,4 mm²

(For cable: max. 1,4 mm²)

Bestellinformation (Order Information)

Art. Nr. (Art. No.):

UEBK-30285 / UEBK-30286

