

Batteriekontakt / Battery Probe - UEBK-30299 / 30259

Material (Material)

Gehäuse: Polyamid PA66 (UL94V-2)

(Frame: Polyamide PA66 (UL94V-2))

Kolben: Messing, vergoldet

(Plunger: Brass, gold plated)

Stifthülse: Messing, vergoldet

(Barrel: Brass, gold plated)

Feder: Edelstahl

(Spring: Stainless Steel)

Elektrische Spezifikation (Electrical specification)

Nennstrom: 10 A

(Rated Current: 10 A)

Kontaktwiderstand: < 25 mΩ

(Contact Resistance: < 25 mΩ)

Mechanische Spezifikation (Mechanical specification)

Kontakte: 6

(No. of contacts: 6)

Max. Hub: 2,55 mm

(Max. travel: 2,55 mm)

Empfohlener Hub: 1,70 mm

(Recommended travel: 1,70 mm)

Federkraft: 1,7 N bei Empfohlenem Hub

(Spring Force: 1,7 N @ recommended travel)

Kabelquerschnitt: max. 1,4 mm²

(Cable cross section: max. 1,4 mm²)

Bestellinformation (Order Information)

Art. Nr. (Art. No.):

UEBK-30299 / UEBK-30259

