

Batteriekontakt / Battery Probe - UEBK-30338 / 30342 / 30339

Material (Material)

Gehäuse: Polyamide PA66 (UL94V-2)

(Frame: Polyamid PA66 (UL94V-2))

Kolben: Messing, vergoldet

(Plunger: Brass, gold plated)

Stifthülse: Messing, vergoldet

(Barrel: Brass, gold plated)

Feder: Edelstahl

(Spring: Stainless Steel)

Elektrische Spezifikation (Electrical specification)

Kontaktwiderstand: < 25 mΩ

(Contact Resistance: < 25 mΩ)

UEBK-30338

Nennstrom pro Kontakt: 12 A

(Rated Current per Contact: 12 A)

UEBK-30342

Nennstrom pro Kontakt: 8 A

(Rated Current per Contact: 8 A)

Mechanische Spezifikation (Mechanical specification)

Kontakte: 2

(No. of contacts: 2)

Max. Hub: 2,65 mm

(Max. travel: 2,65 mm)

Empfohlener Hub: 2,05 mm

(Recommended travel: 2,05 mm)

Für Kabel: max. 1,5 mm²

(For cable: max. 1,5 mm²)

UEBK-30338

Federkraft pro Kontakt: 3,25 N bei
Empfohlenem Hub

(Spring Force per Contact: 3,25 N
@ recommended travel)

UEBK-30342

Federkraft pro Kontakt: 2,0 N bei
Empfohlenem Hub

(Spring Force per Contact: 2,0 N
@ recommended travel)

Bestellinformation (Order Information)

Art. Nr. (Art. No.):

UEBK-30338 / UEBK-30339

UEBK-30342 / UEBK-30339

