




VGRCB-15CP

VGFCB-15CP*

VGRCB-15CP VGFCB-15CPF

The VGRCB-15CP provides 15 contacts for coax, power or a combination of both contact styles. Coax contacts are provided for signals up to 500 Mhz and power signals up to 30Amps / 250VAC. Contacts, blocks and cables sold separately.

Coax Contact Pair Specifications

Voltage	250VAC
Current	1.5 Amps
Contact Resistance	6mΩ
Capacitance	5pf
Inductance	3nH
Bandwidth (-3db roll off)	500 Mhz
Durability	25,000 cycles
Coax Connection Type	Crimp

Power Contact Pair Specifications

Power Contact	30 Amps
---------------------	---------

*Note:

The VGFCB-15CP (shown) has been obsoleted and replaced with the VGFCB-15CPF. Two tooling holes are added to the VGFCB-15CPF block to allow for the alignment pins on a VGRCB-15CPF. The VGFCB-15CPF is fully compatible for all VGRCB-15CP applications.

Ordering Information

Receiver

Receiver Module	VGRCB-15CP
36" Receiver Coax Cable Assy	CR-CA50RG174-36
Receiver Power Contact	CR-610116102

Accessories

Receiver Contact Extraction Tool	VGRXT
--	-------

Fixture

Fixture Module	VGFCB-15CP
36" Fixture Coax Cable Assy	CF-CA50RG174-36
10 AWG Fixture Power Contact	CF-610115102
12 AWG Fixture Power Contact	CF-610115103

Fixture Contact Extract Tool	VGFXT
------------------------------------	-------



Note: The VGR and VGFCB-15CP are obsolete parts and should only be used in applications requiring compatibility with older contact block designs.